



MLA 系列适配器产品目录

电压 \ 功率	5W	10W	12W	15W	18W	24W	36W	45W	25W
3.0V	1.5A	2A	2A	2.5A	3A	*	*	*	双组输出
	2A	2.5A	*	*	*	*	*	*	5V 1.5A
3.3V	1.5A	2A	2A	2.5A	3A	*	*	*	12V 1.5A
	2A	*	*	*	*	*	*	*	*
3.6V	1.5A	2A	*	*	*	*	*	*	*
4.2V	0.7A	2A	*	*	*	*	*	*	*
	0.8A	*	*	*	*	*	*	*	*
	1.2A	*	*	*	*	*	*	*	*
4.5V	0.5A	1.6A	*	*	*	*	*	*	*
	1A	2A	*	*	*	*	*	*	*
5.0V	0.5A	1.5A	2A	2.5A	3A	4A	*	*	*
	1A	2A	*	*	*	*	*	*	*
6.0V	0.5A	1.8A	2A	2.3A	2.8A	3.8A	*	*	*
	1A	*	*	*	*	*	*	*	*
7.5V	0.8A	1.6A	*	*	*	*	*	*	*
9V	0.65A	1.3A	1.3A	1.6A	2A	2.6A	*	*	*
10V	*	1.2A	1.2A	1.5A	1.8A	2.4A	*	*	*
12V	0.5A	1A	1A	1.25A	1.5A	2A	3A	3.8A	*
15V	0.4A	0.8A	0.8A	1A	1.2A	1.6A	2.4A	3A	*
16V	*	*	*	*	*	*	2.3A	2.8A	*
19V	*	*	*	*	*	*	2A	2.3A	*
19.5V	*	*	*	*	*	*	2A	2.3A	*
24V	0.25A	*	*	*	0.75A	1A	1.5A	1.9A	*
36V				0.42A					
48V		0.2A	0.25A	0.31A		0.5A	0.75A	0.94A	





MLA 开关电源适配器技术参数

特征[Feature]:	
超小体积,便于携带 [Super Mini Size and Easy Protatable]	
轻便,自带插头,方便使用 [Light&Convenient Plug In]	
用途[Application]:	
数位相机[Digital Camera]	
光驱 集线器 路由器 [CD-ROM HUB ADSL AP]	
通讯终端设备[Communication Terminals]	
测试设备[Tester Machine]	
任何携带型设备或机器[Any Protatable Device or Machine]	
输入/输出规格[Input/Output Specifications]:	
输入电压[Input Voltage]:	AC 100-240V,50/60Hz
输入电压范围[Range Voltage]:	AC 90--264V,47/63Hz
输出功率[Output Power]:	5-60W
输出电压[Output Voltage]:	3V、5V、12V、24V、48V
过压保护[Over Voltage Protection]:	120%min
过流保护[Over Current Protection]:	120%min
短路保护[Short Protection]:	Auto Recovery
输出电压变动[Load Regulation]:	±5%
一般规格[General Specifications]:	
工作环境温度[Operating Temperature]:	0~40℃
储存温度[Storage Temperature]:	-20~85℃
工作湿度[Operating Relative Humidity]:	5~95%RH
耐压[Withstanding Voltage]:	AC 3000V(Min),5mA(Max)
绝缘阻抗[Insulation Resistance]:	DC 500V 100MΩ(Min)
安規[Safety]: UL/cUL PSE GS BS CE CB FCC SAA CCC BSMI C-TICK	

